



## Tremsil® 600 Silicone Sealant

**Product #** 036390

**Finish/Color** Black

### DESCRIPTION

#### Single-component, neutral-cure silicone sealant for glazing

Tremsil® 600 is a one-part, neutral-cure, medium modulus silicone sealant. The sealant cures to a flexible rubber when exposed to moisture present in the air. Tremsil® 600 is compatible with most common porous and non-porous building component surfaces, making it an excellent sealant for use in commercial construction as well as in a wide variety of high-performance window systems.

### ADVANTAGES AND BENEFITS

With excellent adhesion to a variety of substrates, including glass and metal, one product may be used for a variety of applications on the same job from metal to metal joinery to perimeter beads. - Comes ready-to-use with no mixing required for immediate application with conventional caulking equipment. - Greenguard Gold certification ensures safety for use in the most sensitive indoor environments including hospitals and schools.

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	036390
<b>Brand</b>	Tremco
<b>Base</b>	100% RTV Silicone
<b>Optimal Adherence to</b>	Vinyl, Concrete, Glass, Non-oiled Wood, Plastic, Brick, Aluminum, Painted metal, Stainless Steel, Wood
<b>Features</b>	Fast-Drying, Heavy-Duty, Neutral Cure, Weatherproof, Good Cold Flexibility
<b>Volume</b>	300 ml
<b>Recommended Use</b>	Aluminum Windows, Wood Windows, Vinyl/PVC Windows
<b>Tack-Free / Skin Over Time</b>	Less than 2 hours
<b>Tooling Time</b>	8 to 10 minutes
<b>Packaging Specifications</b>	Plastic Cartridge
<b>VOC Concentration (EPA Method 24)</b>	34 grams per liter
<b>Standards and Certifications</b>	ASTM C920, CAN/CGSB-19.13-M87

### APPLICATION

- Is ideal for use as an in-plant glazing sealant for applications that include, back-bedding, cap, heel and toe beads, and sash joinery. - Is compatible with most common porous and non-porous building components and has excellent adhesion to aluminum, stainless steel, metals, glass, plastics, rigid PVC, wood, brick, concrete and painted surfaces. - Is also designed for application through automated glazing equipment such as x-y tables.

### IMPORTANT INFORMATION

Limitations: - Do not apply to damp or contaminated surfaces - Use with adequate ventilation - Not intended for continuous water immersion

PRODUCT PHOTOS

