



## Alex PLUS Acrylic Latex Caulk with Silicone

**Product #** 150130

**Finish/Color** White

**Color on Application** White

### DESCRIPTION

DAP® ALEX PLUS® Acrylic Latex Caulk Plus Silicone is an excellent quality, all-purpose caulk for sealing a wide variety of interior and exterior surfaces. It contains silicone additives for greater flexibility and adhesion and shrinks less for a durable, waterproof seal. ALEX PLUS® is paintable in just 30 minutes with latex or oil-based paints, saving time.

### ADVANTAGES AND BENEFITS

Advantages and benefits: - All-purpose - Strong multi-surface adhesion - Paint in 30 minutes - Won't shine through or discolor paint - Shrinks less for a durable seal\* - Flexible - Resists cracking and chalking - 100% waterproof seal - Easy water cleanup - Low odor - Cured caulk is mold and mildew resistant - Exceeds ASTM C834 specification - Low VOC - Interior/exterior use

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	150130
<b>Recommended Use</b>	Aluminum Windows, Plastic, Wood Windows, Exterior Trim and Siding, Vinyl/PVC Windows, Metal, Painted Surfaces, Glass, Fiberglass, Door and Window, Wood, Concrete
<b>Base</b>	Siliconized Acrylic Latex
<b>Volume</b>	300 ml
<b>Tooling Time</b>	10 minutes
<b>Brand</b>	DAP
<b>Features</b>	Low VOC (less than 250 g/l), Heavy-Duty, Low Odor, Waterproof, Thermal Resistance, Weatherproof, Good Cold Flexibility, Superior Bond, Wash with Water, Transparent 7 to 14 Days After Application
<b>Freeze/Thaw Stability</b>	Stable
<b>Standards and Certifications</b>	ASTM C834, ASTM C1183

### APPLICATION

Can be used for: - Window frames - Door frames - Baseboards - Molding - Trim - Corner joints - Pipes - Vents - Siding - Other gaps and cracks, especially prior to painting Adheres to the following materials: - Painted and unpainted wood - Aluminum - Most metals - Vinyl - Most plastics - Glass - Drywall - Plaster - Brick - Stone - Concrete - Mortar - Fiber cement - Stucco - Most common building materials

### IMPORTANT INFORMATION

- Apply in temperatures above 4.4 °C - Do not apply when rain or freezing temperatures are forecasted within 24 hours - Cooler temperatures and higher humidity will slow down dry time - Not for continuous underwater use, filling butt joints, surface defects, tuck-pointing, or expansion joints. - Joint size should not exceed 1/2 in (13 mm) wide x 1/2 in (13 mm) deep. If joint depth exceeds 1/2 in (13 mm), use backer rod material - Store caulk away from extreme heat or cold.

PRODUCT PHOTOS

