



## Extended Fitting Kit for Locking Pull Handles

**Product #** 701GHLR110EX170

### DESCRIPTION

**For wood doors**

This fitting kit allows you to use the lock, included with the handle, on a wood door that is 45 mm thick.

### ADVANTAGES AND BENEFITS

Allows you to have matching wood and glass doors.

## REQUIRED PRODUCTS

Requires ONE of the following products

**Sales unit**



**1" (25 mm) Diameter Ladder Back-to-Back with Lock (Convertible) Stainless Steel Handle - Height: 2 210 mm**  
Product # 701GHLR110170

Set

OR



**1" (25 mm) Diameter Ladder Back-to-Back with Lock (Convertible) Stainless Steel Handle - Height: 1 230 mm**  
Product # 701GHLR109170

---

## TECHNICAL SPECIFICATIONS

Product #	701GHLR110EX170
Color/Finish	Stainless Steel
Diameter	30 mm
Door Type	Wood
Door Thickness	45 mm
Thickness	3 mm
Usage	Hinge Door
Length	85 mm
Projection	25 mm
Material	Stainless Steel 304
Screw/Nail	Wood Screw (Included)

## APPLICATION

Ideal for commercial applications such as offices.

## INCLUDED PRODUCT(S)

Connector, cylinder rod, hexagonal key and mounting screw.

## IMPORTANT INFORMATION

Works only with wood doors that are 45 mm thick.

## DISCLAIMER

Note: Picture for visual reference only: actual product may vary from that shown in photo. Be sure to order hardware before beginning fabrication or installation work. Always use the instructions inside the packaging provided by the manufacturer, as the manufacturer reserves the right to make technical changes or modify information without prior notice. All technical drawings and documents contain examples for the assembly of different suppliers' hardware. The customer cannot make any claims based on the use of these documents. No responsibility is assumed for design details relating to a construction or project. At all times, execution and installation must be undertaken by qualified persons. Never exceed the maximum weight or the maximum dimensions recommended by the manufacturer. Always be sure to install the product correctly using the appropriate fixation for your material. Use a dry cloth to remove fragments, dust, and residue (wood and/or aluminum sawdust) from rails before the installation of the hangers. Never use any spray lubricant on these products. Disclaimer: The preceding information as well as any technical recommendations given in writing, verbally or based on tests are provided to the best of our knowledge. However, they are non-binding recommendations only and do not affect your responsibility to determine the correctness of given recommendations and suitability of the product for your particular purposes. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore fall exclusively in your area of responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

**PRODUCT PHOTOS**

