



1" (25 mm) Diameter Ladder Back-to-Back Stainless Steel Handle with Lock - Height: 2 210 mm

Product # 701IN07103D170

DESCRIPTION

For glass 10 to 12 mm thick

TECHNICAL SPECIFICATIONS

Product #	701IN07103D170
Door Type	Glass
Glass Thickness	10 to 12 mm
Color/Finish	Stainless Steel
Function	Back-to-Back Pull Handle, Entrance
Usage	Sliding Door, Hinge Door
Diameter	25 mm
Height	2 210 mm
Projection	80 to 115 mm
Material	Stainless Steel 304
Center to Center Drilling (Spacing)	1 955 mm
Milling Diameter	14 mm
Type	Round
Screw/Nail	Included
Brand	JNF

IMPORTANT INFORMATION

Picture for visual reference only: actual product may vary from that shown in photo. Be sure to order hardware before beginning fabrication or installation work. Always use the instructions inside the packaging provided by the manufacturer, as the manufacturer reserves the right to make technical changes or modify information without prior notice. All technical drawings and documents contain examples for the assembly of different suppliers' hardware. The customer cannot make any claims based on the use of these documents. No responsibility is assumed for design details relating to a construction or project. At all times, execution and installation must be undertaken by qualified persons. Never exceed the maximum weight or the maximum dimensions recommended by the manufacturer. Always be sure to install the product correctly using the appropriate fixation for your material. Use a dry cloth to remove fragments, dust, and residue (wood and/or aluminum sawdust) from rails before the installation of the hangers. Never use any spray lubricant on these products.

INCLUDED PRODUCT(S)

This handle has a small knob on the inside and includes a dust cover for the floor.

DISCLAIMER

The preceding information as well as any technical recommendations given in writing, verbally or based on tests are provided to the best of our knowledge. However, they are non-binding recommendations only and do not affect your responsibility to determine the correctness of given recommendations and suitability of the product for your particular purposes. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore fall exclusively in your area of responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS



