

**Image  
Coming  
Soon**

## Sidelite 4" square Rails

**Product #** 704225049120010

### DESCRIPTION

Square Sidelite Rails are commonly used in large display cases to secure fixed glass panels. They match our door rails, which are also needed to gain access to the display. Sidelite Rails can be used top and bottom for a matching look or with a variety of smaller configuration U-Channels.

End cap sold separately.

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	704225049120010
<b>Glass Thickness</b>	12 mm
<b>Finish</b>	Satin Aluminum
<b>Length</b>	10 ft
<b>Height</b>	4 in
<b>Saddle Size</b>	1/4 in

### IMPORTANT INFORMATION

Glass is installed easily with the 'lift and drop' method using 4" (101.6 mm) Aluminum and Neoprene Setting Blocks. Glass is secured with a Top Load EPDM Roll-in Glazing Gasket that eliminates the messy application of silicone sealant. For safety purposes, use tempered glass. The use of power tools during installation may damage the hinges and decorative hardware. The glass must be shaped according to the section plane provided in the box. Always set the product in a suitable material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. This illustration is provided for visual reference only. Actual product may differ from the illustration. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always use the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may in no case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel. Always make sure that the product is properly installed using suitable fixings to the support material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product.

### DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

---

## PRODUCT PHOTOS

**Image  
Coming  
Soon**