



## Riveo Aqua 01 PRO Kit

**Product #** 705AQUA01171

**Finish** Bright Polished Chrome

### DESCRIPTION

#### Sliding Door System

Set for creating a sliding door system for a frameless glass shower.

### ADVANTAGES AND BENEFITS

- Ideal for use as a shower stall - Features one sliding door and one fixed panel - Minimal hardware gives the appearance of a floating door - Fitting available for 90° return panel (sold separately)

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	705AQUA01171
<b>Application</b>	Single Sliding
<b>Load Capacity</b>	Max. 40 kg
<b>Glass Thickness</b>	8 to 10 mm
<b>Recommended Door Height</b>	Max. 2 000 mm
<b>Max. Fixed Panel Height</b>	Max. 2 010 mm
<b>Recommended Door Width</b>	Max. 1 000 mm
<b>Enclosure Width</b>	Max. 2 000 mm
<b>Recommended Fixed Panel Width</b>	1 160 mm
<b>Brand</b>	Riveo
<b>Material</b>	Stainless Steel: 304

### APPLICATION

Suitable for applications in the hospitality and residential sectors.

### INCLUDED PRODUCT(S)

- Includes hardware for the door and fixed panel. - Includes a recessed handle. Refer to the assembly document for the detailed list. \* Base, faucet and glass are not included.

---

## IMPORTANT INFORMATION

For safety purposes, use tempered glass. The glass must be shaped according to the section plane provided in the box. The use of power tools during installation may damage the hinges and decorative hardware. This illustration is provided for visual reference only. Actual product may vary. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always follow the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may not in any case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must always be done by qualified personnel. Make sure that the product is properly installed using suitable fixtures on the support material. Never exceed the maximum load or size recommended by the manufacturer. Never use a spray lubricant on this product. Maintenance: clean with a soft cloth and soap that is ammonia-free and nonabrasive.

## DISCLAIMER

The preceding information, as well as any technical recommendation given in writing or verbally, whether based on tests or not, is provided to the best of our knowledge. Recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products, as well as the execution of projects based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

## PRODUCT PHOTOS

