



Inset Glass Door Pivot Hinge

Product # 757304140

DESCRIPTION

Right or left opening

The shape and chrome finish of this pivot hinge give a sleek, modern look to glass cabinets and showcases. Designed to open as much to the left as to the right, it is mounted on a glass panel of a thickness varying from 5 mm to 8 mm.

ADVANTAGES AND BENEFITS

- Modern, sleek, and linear style. - Designed for glass cabinets or wooden showcases with glass doors - For glass thicknesses of 5 mm, 6 mm, and 8 mm.

TECHNICAL SPECIFICATIONS

Product #	757304140
Load Capacity	Max. 12 kg
Material	Zinc
Length	65 mm
Width	20 to 23 mm
Height	40 mm
Thickness of Glass	5 to 8 mm
Side	Pair
Finish	Chrome
Width of Door to Respect	Max. 500 mm
Height of Door to Respect	Max. 1 200 mm
Use Type	Glass
Hinge Opening Angle	+150°
Brand	Sugatsune

APPLICATION

- Inset application. - Shaping of the glass panel required with this hinge. - For a maximum door width of 19-11/16' L x 47-1/4" H (500 mm x 1200 mm) per pair. - Maximum glass door weight, 26.5 lb (12 kg) per pair, including all accessories, such as handles, etc.

INCLUDED PRODUCT(S)

-2 Hinge bodies (A and B) -2 Strike plates (screws included) -2 Strike plate nuts -2 Gaskets -6 Glass fixing screws -2 Tension screws -2 Caution stickers

IMPORTANT INFORMATION

This illustration is provided for visual reference only. Actual product may differ from the illustration. For safety purposes, use tempered glass. The use of power tools during installation may damage the hinges and decorative hardware. The glass must be shaped according to the section plane provided in the box. Always set the product in a suitable material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always use the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may in no case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel. Always make sure that the product is properly installed using suitable fixings to the support material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product.

PRODUCT PHOTOS

