

## Translucent Vinyl Angled Edge Wipe

**Product #** 87S0516T30

### DESCRIPTION

#### Without adhesive ribbon

This seal was designed to be used with door and strike jamb extrusions or to be attached to a vertical or horizontal edge. Its leg may be trimmed in the field to fine tune the installation. To attach, use Crystal Clear 2-way tape for a positive, long lasting bond.

### REQUIRED PRODUCTS

Requires ONE of the following products

**Sales unit**



#### Double Sided Polyester Tape With Red Poly Liner

Product # 703HA3641411

Roll of 33 linear meter

OR



#### High Bonding Acrylic Tape

Product # 491206006

Length: 16.5 m      Thickness: 1.5 mm

Roll of 54 linear foot

OR



#### High Bonding Acrylic Tape

Product # 491402006

Length: 33 m      Thickness: 0.5 mm

Roll of 108 linear foot

## TECHNICAL SPECIFICATIONS

<b>Product #</b>	87S0516T30
<b>Glass Thickness</b>	8 to 12 mm
<b>Finish</b>	Translucent
<b>Height</b>	5.5 mm
<b>Width</b>	7.5 mm
<b>Length</b>	3 m
<b>Material</b>	Vinyl

## IMPORTANT INFORMATION

For safety purposes, use tempered glass. Always set the product in a suitable material. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. This illustration is provided for visual reference only. Actual product may vary. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always use the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may not in any case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must always be done by qualified personnel. Make sure that the product is properly installed using suitable fixtures on the support material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product.

## DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

## PRODUCT PHOTOS



