



## Terno Solo Vetro 80 Synchro Hardware Set with One-Way Soft-Close

**Product #** 89270222714A

### DESCRIPTION

#### Synchronize biparting sliding system for glass

The Terno Solo Vetro 80 Synchro hardware set is for two biparting glass doors 5/16 in to 1/2 in (8 mm to 12.7 mm) thick weighing 176 lb (80 kg) each.

- Durable pulley cable system to synchronize two doors to open and close simultaneously in opposite directions
- Includes dry glazing clamping shoes that do not require drilling the glass or adhesive to support the doors
- Includes two soft-close mechanisms to gently slow the doors to a stop
- Ball bearing trolley with anti-derail device

### ADVANTAGES AND BENEFITS

- Quick and simple low-cost installation

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	89270222714A
<b>Roller Position</b>	Upper
<b>Load Capacity</b>	Max. 80 kg
<b>Product type</b>	Hardware Set
<b>Door Material</b>	Glass
<b>Number of Doors</b>	2
<b>Door Width</b>	600 to 1 200 mm
<b>Door Thickness</b>	8 to 12.7 mm
<b>Door Height</b>	Max. 2 743 mm
<b>Brand</b>	Terno

### IMPORTANT INFORMATION

Pictures provided for visual reference only: actual product may vary. All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantity listed in your order are correct before proceeding to checkout. Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. The documentation, drawings and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. Installation of the Product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. Always remove debris / dust / residues (sawdust and / or aluminum) from the rails using a dry cloth before installing carriage bearings. Never spray lubricant.

## DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

## PRODUCT PHOTOS

