



## Hydraulic Self-Closing Bottom Pivot Patch-Fitting Hinge

**Product #** CDHFH100SS

### DESCRIPTION

This hydraulic floor hinge includes a multi adjustable mounting plate and two adjustment valves for closing speed. The open angle is 140° maximum

### ADVANTAGES AND BENEFITS

Designed for several layers of glass Adjustable positions: - forward and backward - left and right - amplitude to adjust the alignment

## TECHNICAL SPECIFICATIONS

<b>Product #</b>	CDHFH100SS
<b>Finish</b>	Brushed Stainless Steel
<b>Glass Thickness</b>	10 to 15 mm
<b>Length</b>	177 mm
<b>Width</b>	55 mm
<b>Load Capacity</b>	Max. 100 kg
<b>Recommended Door Height</b>	Max. 2.2 m
<b>Material</b>	Aluminum
<b>Height</b>	77 mm
<b>Weight Capacity for 2 Hinges</b>	Max. 100 kg
<b>Recommended Location Usage</b>	Interior
<b>Mounting Side</b>	Reversible
<b>Mounting Method</b>	Floor Mount
<b>Usage</b>	Heavy-Duty
<b>Max. Door Width for 2 Hinges</b>	Max. 1 000 mm

## APPLICATION

Installs directly on a floor surface.

## IMPORTANT INFORMATION

For safety purposes, use tempered glass. The glass must be shaped according to the section plane provided in the box. The use of power tools during installation may damage the hinges and decorative hardware. Never use a spray lubricant on this product. Maintenance: clean with a soft cloth and soap that is ammonia-free and nonabrasive. This illustration is provided for visual reference only. Actual product may vary. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always follow the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may not in any case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must always be done by qualified personnel. Make sure that the product is properly installed using suitable fixtures on the support material. Never exceed the maximum load or size recommended by the manufacturer.

## DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

## PRODUCT PHOTOS

