



Tremco® 830

Product # D030036

Finish Black

Volume 300 ml

Packaging Specifications Cardboard Cartridge

DESCRIPTION

Thermoplastic, Elastomeric Glass and Siding Sealant

Tremco 830 is a one-part, thermoplastic elastomer that provides a high-performance, flexible seal in glazing and siding applications. Not for use in the United States.

ADVANTAGES AND BENEFITS

- Fast skinning, fast cure through. - Easy gunning. - Excellent weather and UV resistance. - Can be painted with latex paint

TECHNICAL SPECIFICATIONS

Product #	D030036
Brand	Tremco
Product Type	Thermoplastic Elastomere
Ideal Use	Aluminum Windows, Wood Windows, Vinyl (PVC) Windows, Exterior Trim & Siding, Outside
Base	Elastomeric Polymer
Optimal adherence to	Concrete, Non-oiled Wood, Brick, Aluminum, Vinyl, Masonry
Tooling Time	Immediately tool the sealant
Properties	Paintable

APPLICATION

Basic Uses: - Can be used in glazing applications for face bedding and cap beads and sealing miter joints in window profiles. - Can be used for siding applications with sill trim, flashings, fascia, J-trim, F-channel and crown molding. - Can also be used for sealing perimeters of wood, PVC and aluminum residential windows and doors.

IMPORTANT INFORMATION

- Not for use in the United States. - Do not apply Tremco 830 over damp or contaminated surfaces. - Do not use in contact with polystyrene, insulated glass seals or laminated glass. - Always utilize the accompanying MSDS for information on Personal Protective - Equipment (PPE) and health hazard

PRODUCT PHOTOS

