



Right-Angle Glass Clamp Open on Three Sides to be in Center

Product # GMGC39138BN

DESCRIPTION

Solid brass glass clamps

Features removable plates on either side: simply remove the two Phillips screws. Sold with flat bottom; radius available on order. Quality plated chrome or brushed nickel finish, as solid as brass clips.

Glass clamps designed for balusters and railings. Available in different finishes and for several installation configurations. Not recommended for use on the West Coast because of the salt in the sea air.

ADVANTAGES AND BENEFITS

The glass width refers to the maximum width to be used per product. There may be a gap between the external plate and the clamp when using these glass thicknesses.

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|----------------|
| Product # | GMGC39138BN |
| Recommended Location Usage | Interior |
| Finish | Brushed Nickel |
| Glass Drilling | Not Required |
| Safety Glass Thickness | 10 mm |
| Width | 49 mm |
| Length | 49 mm |
| Material | Solid Brass |
| Baluster Post Type | Square Tube |
| Milling C/C | 16 mm |

APPLICATION

These clamps are for interior use.

IMPORTANT INFORMATION

For safety purposes, use tempered glass. The use of power tools during installation may damage the hinges and decorative hardware. The glass must be shaped according to the section plane provided in the box. Always set the product in a suitable material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. This illustration is provided for visual reference only. Actual product may differ from the illustration. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always use the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may in no case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel. Always make sure that the product is properly installed using suitable fixings to the support material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product.

DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

