



Adjustable Height Glass Mount Bracket with Weld-On Caliper

Product # HR14015900012

DESCRIPTION

Long-stem and height-adjustable for welding tube

With its simple design, this stainless steel adjustable inline bracket is ideal for all your handrail and staircase projects. Designed to support round or flat surface handrails off a glass panel and allows you to adjust to your desired height. Easy to install, the bracket must pass through the glass for installation, and the handrail must be welded on.

ADVANTAGES AND BENEFITS

It comes in finish 304, strictly for interior use, and finish 316 for interior and exterior use.

TECHNICAL SPECIFICATIONS

Product #	HR14015900012
Type of Mounting	Glass Mount
Handrail Type	Flat Tubing, Round Tubing
Recommended Location Usage	Interior, Exterior
Adjustment	Adjustable Height
Finish	Stainless Steel
Height	1.18 to 3.15 in
Projection	3.23 in
Material	Stainless Steel 316
Safety Glass Thickness	12 to 30 mm
Glass Drilling	Required
Category	Brackets
Thread Type	M8
Milling Diameter	14 to 15 mm

APPLICATION

- Use the HR94051151614 screw for a steel handrail installation

IMPORTANT INFORMATION

For safety purposes, use tempered glass. The use of power tools during installation may damage the hinges and decorative hardware. The glass must be shaped according to the section plane provided in the box. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. This illustration is provided for visual reference only. Actual product may differ from the illustration. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always use the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may in no case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel. Always make sure that the product is properly installed using suitable fixings to the support material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product.

DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

