



Elbow with Adjustable Rotation Angle

Product # HR18620838170

DESCRIPTION

Pivoting elbow

Articulated elbow designed to personalize tubing handrails.
Links two round tubes to create a corner handrail.
The elbow is held with an inside mounting screw.
Simply unscrew it to separate the two sections and create the desired angle before screwing again.

ADVANTAGES AND BENEFITS

Thanks to its design, the elbow can be installed in various angles. Easy to use, simple insert and glue the interior connector to each end of the round tubes.

REQUIRED PRODUCTS

Requires the following products

Sales unit



Stainless Steel Glue Activator

Product # HR19133100001

AND



Stainless Steel Glue

Product # HR19133100000

TECHNICAL SPECIFICATIONS

Product #	HR18620838170
Handrail Type	Round Tubing
Finish	Stainless Steel
Recommended Location Usage	Interior, Exterior
Material	Stainless Steel 316
Handrail Size	ø 38.1 mm (1 1/2")
Baluster Post Size	ø 38.1 mm (1 1/2")
Curvature angle	90°
Thickness	2 mm
Category	Connectors
Baluster Post Type	Round Tube

APPLICATION

Ideal for architectural projects such as the installation of stairs and glass balusters, with cables or rods. A strand of glue during assembly helps to solidify and better secure the connection between the components.

INCLUDED PRODUCT(S)

Includes an M8 bolt to keep the two sections together.

IMPORTANT INFORMATION

This illustration is provided for visual reference only. Actual product may vary. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always follow the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may not in any case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must always be done by qualified personnel. Make sure that the product is properly installed using suitable fixtures on the support material. Never exceed the maximum load or size recommended by the manufacturer.

DISCLAIMER

The preceding information, as well as any technical recommendation given in writing or verbally, whether based on tests or not, is provided to the best of our knowledge. Recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products, as well as the execution of projects based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

