



PanelGrip®2 Aluminum Dry-Glaze Base Shoe

Product # HRTV0079132210

Type of Mounting Floor Mount

Base section hole drilling patterns Counter Bore

Length 10 ft

Packaging format Length of 10 linear foot

DESCRIPTION



PanelGrip®2 facilitates the quick assembly of structural glass railing without messy fillers or special tools resulting in significant savings in labor and shipping costs.

ADVANTAGES AND BENEFITS

* Reduce Labor Costs up to 80% - No setting blocks, no plumbing of glass, no multiple pours of cement, no waiting for cement to cure, no messy clean-up * Broadest Grip Range of any Dry Glaze System -- Made for range of 1/2" to 13/16" tempered and laminate glass (12.7 mm to 21.5 mm) * No Special Tools Required -- All you need is an Allen wrench for installation or removal * No Mess -- No mixing and pouring of expansion cement, no running of cement on incline

REQUIRED PRODUCTS

Requires ONE of the following products

			Sales unit
	PanelGrip®2 Locking Mechanism		Set
	Product # HRA42PG212		
	Safety Glass Thickness: 12 mm	Finish: Black	
OR			
	PanelGrip®2 Locking Mechanism		Set
	Product # HRA42PG219		
	Safety Glass Thickness: 19 mm	Finish: White	

TECHNICAL SPECIFICATIONS

Product #	HRTV0079132210
Safety Glass Thickness	12.7 to 21.5 mm
Recommended Location Usage	Interior, Exterior
Finish	Mill Finish
Height	4 1/8 in
Width	2 3/4 in
Material	Aluminum 6005-T5
Glass Drilling	Not Required
Category	Base Shoes

IMPORTANT INFORMATION

The PanelGrip®2 base shoe and mechanism are sold as a system and are subject to one or more of the following patents: US7730682, US8181405, NZ581456, CA2697162, EP2171180 and/or AU2008282693

PRODUCT PHOTOS

