



90° Glass-to-Wall or Post Magnetic Safety Gate Latch

Product # PGLSQPG090E170

DESCRIPTION

Magnetic Latch

This magnetic latch features a side pull latch to further lock the glass door. Ideal for corner joining a glass panel and a wall or a post pole in a pool area.

ADVANTAGES AND BENEFITS

- Gives an exceptional clear view in exterior spaces - Ideal for use on pool gates - Weatherproof

TECHNICAL SPECIFICATIONS

Product #	PGLSQPG090E170
Type of Mounting	Wall Mount, Post Mount
Safety Glass Thickness	12 mm
Finish	Stainless Steel
Height	100 mm
Width	31.5 mm
Length	85 mm
Material	Stainless Steel 316
Glass Drilling	Required
Recommended Location Usage	Interior, Exterior
Mounting Side	Reversible
Product Type	Bolt
Milling C/C	80 mm
Milling Diameter	16 mm

APPLICATION

Glass safety barrier around a pool or terrace. - Designed to make the junction between a glass panel and a flat substrate. - Drilling of the glass required for installation.

INCLUDED PRODUCT(S)

Screw caps designed for the black side pull latch included

IMPORTANT INFORMATION

The use of a magnetic latch with a gravity hinge maximizes safety and reduces access to the water. These components help prevent drowning, but do not replace close monitoring.

DISCLAIMER

This illustration is provided for visual reference only. Actual product may differ from the illustration. For safety purposes, use tempered glass. The glass must be shaped according to the section plane provided in the box. Always set the product in a suitable material. Never exceed the load or maximum size recommended by the manufacturer. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always use the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may in no case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel.

PRODUCT PHOTOS

