

1-1/4" Flush Mount Standoff Cap

Product # SCC125038170

DESCRIPTION

Designed to be used with 1-1/4" stand off bases (5/16-18 thread) and with minimum material thickness of 3/8" (9.5 mm). Overall length of fastener is 7/8" (22 mm).

Overall length including plastic insert washer is 1-3/16" (30 mm), overall depth of insert washer 5/16" (8 mm).



REQUIRED PRODUCTS

Requires the following products



1-1/4" Diameter Solid Metal Standoff Base

TECHNICAL SPECIFICATIONS

Product #	SCC125038170
Diameter	1 1/4 in
Thickness	3/8 in
Finish	Brushed Stainless Steel
Threaded	5/16" - 18
Height	22 mm
Material	Stainless Steel: 303
Type	Low-Profile

APPLICATION

Requires: 3/4" diameter hole and 1-1/2 countersunk hole (depth varies by material thickness).

IMPORTANT INFORMATION

For safety purposes, use tempered glass. The use of power tools during installation may damage the hinges and decorative hardware. The glass must be shaped according to the section plane provided in the box. Always set the product in a suitable material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. This illustration is provided for visual reference only. Actual product may differ from the illustration. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always use the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may in no case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel. Always make sure that the product is properly installed using suitable fixings to the support material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product.

INCLUDED PRODUCT(S)

A 1" 5/16x18 assembly screw is included

DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

