



Pivot Hinge for Glass Door Recessed Within Furniture or Cabinet

Length

40 mm

41 mm

Width

11.5 mm

12 mm

Height

13 mm

14.9 mm

15 mm

Thumb Screws

Metal

Plastic

Finish



Black



Chrome



Satin Chrome



Satin Nickel

Packaging format

Pair

Blister of 2 units

Pair

Bag of 2 units

DESCRIPTION

No drilling of glass

AVAILABLE PRODUCTS

Product #	Length	Width	Height	Thumb Screws	Finish	Packaging format
2001140	40 mm	12 mm	13 mm	Metal	Chrome	Pair
BP2001140	40 mm	12 mm	13 mm	Metal	Chrome	Bag of 2 units
576FBR	40 mm	12 mm	13 mm	Plastic	Black	Blister of 2 units
480612145	41 mm	11.5 mm	14.9 mm	Plastic	Satin Chrome	Pair
480612185	41 mm	11.5 mm	14.9 mm	Plastic	Satin Nickel	Pair
200190	41 mm	12 mm	15 mm	Plastic	Black	Pair
BP200190	41 mm	12 mm	15 mm	Plastic	Black	Pair

TECHNICAL SPECIFICATIONS

Material	Steel
Thickness of Glass	5 to 6 mm
Load Capacity	Max. 2.5 kg
Dimensions to subtract from the height	3/8 in
Dimensions to subtract from the width	3/32 in
Height of Door to Respect	Max. 800 mm
Width of Door to Respect	Max. 500 mm
Screw/Nail	Included

IMPORTANT INFORMATION

Please refer to technical drawing for detailed measurements. Note: The dimensions indicated above are guidelines that provide satisfactory results in most cases. For more precise installations, your own calculations can be made when you have hinges and cabinets in hand.

APPLICATION

Glass Preparation: - Glass Height: Opening Minus 3/8". - Single Door Width: Opening Minus 3/32". - Double Door Width: Opening Minus 5/64". Press fit bushing.

INCLUDED PRODUCT(S)

Screws are included.

PRODUCT PHOTOS

