


Continuous Geared Concealed Leaf Aluminum Hinges

Usage

Heavy-Duty

Standard Use

Finish



Length

83 in

95 in

DESCRIPTION

112/112HD series, commercial-grade hinges.

- Manufactured with thrust bearings spaced along hinge length on 5-1/8" centers.
- Cover channel, bearing spacing, and screw fastener location designed for heavier loads.
- Frame leaf alignment rib for proper hinge and door location.

AVAILABLE PRODUCTS

Product #	Usage	Finish	Length
780112183313	Heavy-Duty	Bronze	83 in
780112195313	Heavy-Duty	Bronze	95 in
78011218310	Heavy-Duty	Satin Aluminum	83 in
78011219510	Heavy-Duty	Satin Aluminum	95 in
780112083313	Standard Use	Bronze	83 in
78011208310	Standard Use	Satin Aluminum	83 in

TECHNICAL SPECIFICATIONS

Mounting Type	Concealed
Load Capacity	Max. 200 lb
Door thickness	Max. 1 3/4 in
Material	Anodized Aluminum 6063-T6

INCLUDED PRODUCT(S)

- #12-24 X 11/16" Flat Head Self-Drill Screws

IMPORTANT INFORMATION

- Fire rating: up to 3 hours metal and 90 minutes wood composite (with studs) - Heavy-duty hinges are designed for high-frequency use and contain twice as many bearings than standard duty hinges

PRODUCT PHOTOS

