





## Dow Corning® Contractors Weatherproofing Sealant

### Finish/Color



Black



Bronze



Gray



Satin  
Aluminum



White

### Volume

305 ml

591 ml

### Packaging Specifications

Plastic  
Cartridge

Sausage

## DESCRIPTION

### Medium-modulus silicone joint sealant

Dow Corning® Contractors Weatherproofing Sealant (CWS) is a one-part, moisture cure, medium modulus sealant that provides durable, flexible, watertight joints and offers outstanding unprimed adhesion to most nonporous substrates.

It is specifically developed for sealing dynamically moving joints.

The sealant is easily gunnable in all weather conditions from -29 to 49°C (-20 to 120°F). Because it requires no mixing and a smaller joint ratio, it is an economical, high-performance alternative to other sealant options with a ±40 percent movement capability.

Dow Corning Contractors Weatherproofing Sealant meets or exceeds the requirements of:

- ASTM C 920, Type S, Grade NS, Class 35, Use NT, M, A, and O (granite).

## ADVANTAGES AND BENEFITS

- Primerless on most common nonporous building substrates. - Balanced adhesive strength, medium modulus and high recovery. - Easily gunnable in all weather conditions.

## AVAILABLE PRODUCTS

Product #	Finish/Color	Volume	Packaging Specifications
<b>SACWSBL</b>	Black	305 ml	Plastic Cartridge
<b>SACWSBLSG</b>	Black	591 ml	Sausage
<b>SACWSBR</b>	Bronze	305 ml	Plastic Cartridge
<b>SACWSBRSG</b>	Bronze	591 ml	Sausage
<b>SACWSGSG</b>	Gray	591 ml	Sausage
<b>SACWSASG</b>	Satin Aluminum	591 ml	Sausage
<b>SACWSW</b>	White	305 ml	Plastic Cartridge
<b>SACWSWSG</b>	White	591 ml	Sausage

## TECHNICAL SPECIFICATIONS

<b>Brand</b>	Dow Corning
<b>Base</b>	100% RTV Silicone
<b>Optimal Adherence to</b>	Masonry, Concrete
<b>Features</b>	Neutral Cure
<b>Recommended Use</b>	Expansion Joints, Aluminum Windows, Wood Windows, Curtain-Window Wall Systems, Vinyl/PVC Windows
<b>Tack-Free / Skin Over Time</b>	3 to 6 hours
<b>Tooling Time</b>	Immediately tool the sealant
<b>VOC Concentration (EPA Method 24)</b>	35 grams per liter

## APPLICATION

Sealing dynamically moving joints such as expansion and control joints, concrete panel joints, tilt-up panel joints, curtainwall joints, perimeter caulking (windows, doors, panels, EIFS, bedding of mullions, panels, and frames, etc.).

## IMPORTANT INFORMATION

This product is neither tested nor represented as suitable for medical or pharmaceutical uses. Dow Corning Contractors Weatherproofing Sealant is not recommended for: \* Silicone structural glazing \* Application in confined areas without proper ventilation \* Joints under constant water submersion

PRODUCT PHOTOS

