



## Protecto Seal 45(TM) Waterproofing Membrane

### Width

6 in	9 in	12 in	36 in
------	------	-------	-------

### DESCRIPTION

Protecto Seal 45 is a 45 mil SBS modified rubberized asphalt self-adhered waterproofing membrane with a tough cross laminated polyethylene film laminated to an aluminum foil for UV resistance and weatherability.

- UV rated for long term exposure.
- Fully adhered system.
- Aluminum foil facer film for added sealant adhesion.
- Seals around properly installed fasteners.

## AVAILABLE PRODUCTS

Product #	Width
PROSEAL455006	6 in
PROSEAL455009	9 in
PROSEAL455012	12 in
PROSEAL455036	36 in

## TECHNICAL SPECIFICATIONS

Length	50 ft
--------	-------

## APPLICATION

Used as a complete waterproof membrane for commercial window and door flashings, skylights, parapet walls, vent stacks, metal buildings. Also used as a system for complete roof coverage on low-pitched and porch roofs, mobile home roofs, RV's, gutters, valleys and HVAC units. For window and door applications: Apply first piece of Protecto Seal 45 to the rough opening sill and firmly roll into place using a hand roller (J-roller, Laminate roller) to smooth out any wrinkles, air bubbles or creases that would allow water to migrate behind the membrane.

---

## PRODUCT PHOTOS

