



90° Glass-to-Wall Clamp - Rounded

Finish

Bright Polished Chrome

Brushed Nickel

Matte Black

Matte Oiled Bronze

DESCRIPTION

Used to secure fixed panels of glass for frameless shower enclosures. Mounts directly to the wall, ceiling or floor to secure vertical fixed glass panels.

ADVANTAGES AND BENEFITS

- Maintains a frameless appearance. - Provides a clean looking alternative to U-Channel.

AVAILABLE PRODUCTS

Product #	Finish
SC1RD90W140	Bright Polished Chrome
SC1RD90W195	Brushed Nickel
SC1RD90W900	Matte Black
SC1RD90WORB	Matte Oiled Bronze

TECHNICAL SPECIFICATIONS

Application	Fixed Screen, Corner Shower, Neo-Angle Shower, Door and Panel
Milling Diameter	16 to 19 mm
Glass Thickness	10 to 12 mm
Height	44.45 mm
Length	44.45 mm
Material	Solid Brass
Style	Rounded

APPLICATION

Glass fabrication required to accommodate clamps. Clearance between the glass and wall is from 5/32" to 3/16" (4 to 5 millimeter). Clear silicone can be used to seal the gap and provide a clean, water-tight appearance.

IMPORTANT INFORMATION

For safety purposes, use tempered glass. The use of power tools during installation may damage the hinges and decorative hardware. The glass must be shaped according to the section plane provided in the box. Always set the product in a suitable material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. This illustration is provided for visual reference only. Actual product may differ from the illustration. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always use the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may in no case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel. Always make sure that the product is properly installed using suitable fixings to the support material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product.

DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

