





Aerosol Spray Paint

Finish



DESCRIPTION

fast-drying acrylic lacquer

MG Touch Up Spray Paint is a fast-drying acrylic lacquer which offers excellent adhesion, flexibility and cold check resistance. The finish is extremely hard and durable. In addition, it offers good resistance to detergent, water, abrasion, heat and alcohol. Vehicle: Modified acrylic lacquer Tack-free aerosol: 8 minutes Recoat aerosol: 2 minutes or any time thereafter Full cure: 24 hours to one week depending on the number of recoats, temperature and humidity. Full cure can be accelerated with heat. Full cure is complete when finish is odorless. Do not cure at temperatures above 65°C. Recommended Film Thickness

AVAILABLE PRODUCTS

| Product # | Finish |
|-----------|-------------------------|
| D010307 | Bright Polished White |
| D010306 | Brown Matte Curtain |
| D010301 | Clear Anodized Aluminum |
| D010302 | Sandalwood Qu-Coat Matt |

Wet 3.9 to 5.6 mils (100 to 140 microns). Dry 0.7 to 1.0 mils (18 to 25 microns).

TECHNICAL SPECIFICATIONS

| Material Modified Acrylic Lacquer |
|-----------------------------------|
|-----------------------------------|

APPLICATION

Surface Preparation All surfaces must be clean and dry as well as free of dust, grease, oil, etc. If you are touching up or spraying over conventional finishes, test for compatibility. Product is most suitable for touching up baked finishes or UV-cured finished surfaces.

IMPORTANT INFORMATION

Special Instructions It is recommended that the customer test this product before use. Directions Aerosols: Shake can well before using. Spray with an even sweeping motion 6 to 10 inches (15-25 cm) from surface. Apply 2 or 3 coats as desired, waiting approximately 2 minutes between coats. For best results apply at room temperature (21°C). High temperature and high humidity can cause surface blushing.



PRODUCT PHOTOS

