



Thermoplastic

Finish

Clear

White

DESCRIPTION

Highly adhesive flexible sealant

Formulated from a blend of polymers to produce a highly adhesive flexible sealant specifically developed for use as a building joint sealant. Formulated to produce 100% cohesive failure in peel adhesion tests on a variety of typical substrates.

For interior/exterior joints that have up to +/- 40% joint movement and may be periodically immersed in water.

For use in sealing, caulking and glazing applications on substrates of glass, metal, concrete, wood, vinyl and masonry.

Specifically recommended for perimeter caulking of windows, doors, panels, panel to panel joints, frames, toe, cap, and heel beads and back bedding

AVAILABLE PRODUCTS

Product #	Finish
SA1010C	Clear
SA1010W	White

TECHNICAL SPECIFICATIONS

Brand	Guertin
Product Type	Thermoplastic Elastomere
Ideal Use	Aluminum Windows, Wood Windows, Vinyl (PVC) Windows, Exterior Trim & Siding, Outside
Base	Elastomeric Polymer
Optimal adherence to	Concrete, Non-oiled Wood, Brick, Aluminum, Granite, Vinyl
Tooling Time	Immediately tool the sealant
Volume	300 ml
Properties	Paintable
Packaging Specifications	Cardboard Cartridge

APPLICATION

Perimeter sealing and capping Primary & secondary sealing Small joint sealing Insulation adhesive

PRODUCT PHOTOS

