



## Siliconized Acrylic Latex

### Packaging Specifications

Cardboard  
Cartridge

Pail

### Volume

300 ml

15 l

### Weight

10.56 oz

63 lb

## DESCRIPTION

### One-component, pure acrylic emulsion base compound

A one-component, pure acrylic emulsion base compound suitable for sealing, caulking and glazing application in buildings on substrates of glass, architectural aluminum, concrete or wood.

## ADVANTAGES AND BENEFITS

Features: Excellent adhesion and controlled recovery, non-staining, no primer or surface conditioner needed, smooth appearance, excellent tooling, quick skinning, will not sag and weather resistant.

## AVAILABLE PRODUCTS

Product #	Packaging Specifications	Volume	Weight
SA1022BF	Cardboard Cartridge	300 ml	10.56 oz
SA1022BFL	Pail	15 l	63 lb

## TECHNICAL SPECIFICATIONS

Brand	Guertin
Finish	Beige
Product Type	Glazing Putty
Base	Acrylic Latex Siliconized
Ideal Use	Aluminum Windows, Wood Windows
Optimal adherence to	Concrete, Glass, Non-oiled Wood, Aluminum
Properties	Paintable

## APPLICATION

For caulking: Use when perimeter caulking (windows, doors, panels), control joints, panel to panel joints, bedding of mullions, panels and frames, etc. For glazing: Toe bead, cap bead, heel bead, back bedding, etc.

---

## PRODUCT PHOTOS

