




Aluminum Door Sweep with Nylon Brush

Color/Finish



Thickness

7/32 in	1/4 in	3/8 in	7/16 in
---------	--------	--------	---------

Standards and Certifications

Not Certified	ASTM-E152 / CAN/ULC- S104 / NFPA- 252 / UBC-7- 2-94 / CFSM 43.7	ASTM-E152 / CAN/ULC- S104 / NFPA- 252 / UBC-7- 2-94 / UL- 10(b)	UL10C / NFPA-252 / UBC-7-2-94 / UL-10(b) / ANSI/BHMA A156.21-2006 / ANSI/BHMA A156.22-2005 / ANSI/BHMA A156.26-2005 / UL1784- 2001
---------------	--	--	---

Height

1/4 in	3/8 in	5/8 in	1 in
--------	--------	--------	------

Width

25/32 in	7/8 in	1 in	1 7/8 in	2 3/32 in
----------	--------	------	----------	-----------

Length

36 in	48 in	72 in	84 in	96 in
-------	-------	-------	-------	-------

Material

Aluminum	Anodized Aluminum
----------	-------------------

Packaging format

Per unit	Set	Length
----------	-----	--------

DESCRIPTION

Weatherstrip and astragal

AVAILABLE PRODUCTS

Product #	Color/Finish	Thickness	Standards and Certifications	Height	Width	Length	Material	Packaging format
WSDS148B	Bronze	1/4 in	ASTM-E152 / CAN/ULC-S104 / NFPA-252 / UBC-7-2-94 / CFSM 43.7	5/8 in	7/8 in	36 in	Anodized Aluminum	Length
WSDS148B4	Bronze	1/4 in	ASTM-E152 / CAN/ULC-S104 / NFPA-252 / UBC-7-2-94 / CFSM 43.7	5/8 in	7/8 in	48 in	Anodized Aluminum	Length
WSDS148B6	Bronze	1/4 in	ASTM-E152 / CAN/ULC-S104 / NFPA-252 / UBC-7-2-94 / CFSM 43.7	5/8 in	7/8 in	72 in	Anodized Aluminum	Length
WSDS148B8	Bronze	1/4 in	ASTM-E152 / CAN/ULC-S104 / NFPA-252 / UBC-7-2-94 / CFSM 43.7	5/8 in	7/8 in	96 in	Anodized Aluminum	Length
WSDS149B	Bronze	1/4 in	ASTM-E152 / CAN/ULC-S104 / NFPA-252 / UBC-7-2-94 / CFSM 43.7	1 in	1 7/8 in	36 in	Anodized Aluminum	Length
WSDS149B7	Bronze	1/4 in	ASTM-E152 / CAN/ULC-S104 / NFPA-252 / UBC-7-2-94 / CFSM 43.7	1 in	1 7/8 in	84 in	Anodized Aluminum	Length
WSDS149B8	Bronze	1/4 in	ASTM-E152 / CAN/ULC-S104 / NFPA-252 / UBC-7-2-94 / CFSM 43.7	1 in	1 7/8 in	96 in	Anodized Aluminum	Length
WSDS110A	Mill Finish	1/4 in	Not Certified	1/4 in	25/32 in	36 in	Aluminum	Length
WSDS144	Mill Finish	7/16 in	Not Certified	3/8 in	1 in	36 in	Aluminum	Length
WSDS1444	Mill Finish	7/16 in	Not Certified	3/8 in	1 in	48 in	Aluminum	Length
WSDS1448	Mill Finish	7/16 in	Not Certified	3/8 in	1 in	96 in	Aluminum	Length
KNW2584	Satin Aluminum	7/32 in	ASTM-E152 / CAN/ULC-S104 / NFPA-252 / UBC-7-2-94 / UL-10(b)	3/8 in	7/8 in	84 in	Anodized Aluminum	Per unit
WSDS148	Satin Aluminum	1/4 in	ASTM-E152 / CAN/ULC-S104 / NFPA-252 / UBC-7-2-94 / CFSM 43.7	5/8 in	7/8 in	36 in	Anodized Aluminum	Length
WSDS1484	Satin Aluminum	1/4 in	ASTM-E152 / CAN/ULC-S104 / NFPA-252 / UBC-7-2-94 / CFSM 43.7	5/8 in	7/8 in	48 in	Anodized Aluminum	Length
WSDS1488	Satin Aluminum	1/4 in	ASTM-E152 / CAN/ULC-S104 / NFPA-252 / UBC-7-2-94 / CFSM 43.7	5/8 in	7/8 in	96 in	Anodized Aluminum	Length
WSDS149	Satin Aluminum	1/4 in	ASTM-E152 / CAN/ULC-S104 / NFPA-252 / UBC-7-2-94 / CFSM 43.7	1 in	1 7/8 in	36 in	Anodized Aluminum	Length
WSDS149C7	Satin Aluminum	1/4 in	ASTM-E152 / CAN/ULC-S104 / NFPA-252 / UBC-7-2-94 / CFSM 43.7	1 in	1 7/8 in	84 in	Anodized Aluminum	Length
WSDS1487	Satin Aluminum	1/4 in	UL10C / NFPA-252 / UBC-7-2-94 / UL-10(b) / ANSI/BHMA A156.21-2006 / ANSI/BHMA A156.22-2005 / ANSI/BHMA A156.26-2005 / UL1784-2001	5/8 in	7/8 in	84 in	Anodized Aluminum	Length
KNW24S36	Satin Aluminum	3/8 in	ASTM-E152 / CAN/ULC-S104 / NFPA-252 / UBC-7-2-94 / UL-10(b)	1 in	2 3/32 in	36 in	Anodized Aluminum	Set
KNW24S48	Satin Aluminum	3/8 in	ASTM-E152 / CAN/ULC-S104 / NFPA-252 / UBC-7-2-94 / UL-10(b)	1 in	2 3/32 in	48 in	Anodized Aluminum	Per unit

TECHNICAL SPECIFICATIONS

Door Type	Steel, Aluminum Frame
-----------	-----------------------

PRODUCT PHOTOS

