



### **RTS88 Series Overhead Concealed Door Closers**

#### Force #

#3 #4

#### **Type**

105° Hold Open 105° Hold Open (Barrier Free) 105° Non-Hold Open 105° Non-Hold Open (Barrier Free) 90° Hold Open

90° Non-Hold Open

#### **Spindle Type**

Extended Spindle

Regular Spindle

### **Spindle Length**

1/2 in

3/4 in

#### **DESCRIPTION**

The DORMA RTS88 overhead concealed door closer offers the perfect solution to those seeking the aesthetic advantages of a concealed door closer.

The RTS88 closer has a compact body size which fits into a 1-3/4" × 4" header for aluminum frames and is also easily adaptable to wood and hollow metal frame configurations. Openings fitted with the RTS88 are capable of 90° or 105° maximum opening door swing, trim conditions permitting. Sweep and latch closing speeds are controlled by two non-critical temperature compensating valves to ensure constant closing speeds even under the most extreme temperature conditions. A built-in pressure relief valve protects the closer from abuse due to forced closing. A cushion at 90° or 105°, depending on the model selected, helps protect the door, frame, and adjoining structure.

The RTŠ88 may be used on doors weighing up to a maximum of 250 lb (interior) or 200 lb (exterior), including all hardware. The closer may be used on exterior doors up to a maximum width of 3"-6" and interior doors up to a maximum width of 4'.



## **AVAILABLE PRODUCTS**

Product #	Force #	Туре	Spindle Type	Spindle Length
RTS88105HOL	#3	105° Hold Open	Extended Spindle	3/4 in
RTS88105HO	#3	105° Hold Open	Regular Spindle	1/2 in
RTS88105HOLBF	#3	105° Hold Open (Barrier Free)	Extended Spindle	3/4 in
RTS88105NHOL	#3	105° Non-Hold Open	Extended Spindle	3/4 in
RTS88105NHO	#3	105° Non-Hold Open	Regular Spindle	1/2 in
RTS88105NHOLBF	#3	105° Non-Hold Open (Barrier Free)	Extended Spindle	3/4 in
RTS8890HOL	#3	90° Hold Open	Extended Spindle	3/4 in
RTS8890HO	#3	90° Hold Open	Regular Spindle	1/2 in
RTS8890NHOL	#3	90° Non-Hold Open	Extended Spindle	3/4 in
RTS8890NHO	#3	90° Non-Hold Open	Regular Spindle	1/2 in
RTS88105NHOLSZ4	#4	105° Non-Hold Open	Extended Spindle	3/4 in
RTS88105NHOSZ4	#4	105° Non-Hold Open	Regular Spindle	1/2 in

# **TECHNICAL SPECIFICATIONS**

Weight Capacity	200 to 250 lb
Door Width - Interior	Max. 48 in
Door Width - Exterior	Max. 42 in
Guarantee	5 year guarantee
Color/Finish	Satin Aluminum
Door Type	Glass, Aluminum Frame
Standards and Certifications	ANSI A156.4, ADA



# PRODUCT PHOTOS

