



Slot Mount Standoff Post

Glass Thickness

6 mm	10 mm	12 mm
------	-------	-------

Finish

Bright Polished Chrome	Brushed Stainless Steel	Satin Chrome
------------------------	-------------------------	--------------

Material

 Solid Brass	 Stainless Steel
--	--

DESCRIPTION

Solid 1-1/4" machined base

ADVANTAGES AND BENEFITS

No fabrication required

AVAILABLE PRODUCTS

Product #	Glass Thickness	Finish	Material
BPBR1006140	6 mm	Bright Polished Chrome	Solid Brass
BPBR1006170	6 mm	Brushed Stainless Steel	Stainless Steel
BPBR1006145	6 mm	Satin Chrome	Solid Brass
BPBR1010140	10 mm	Bright Polished Chrome	Solid Brass
BPBR1010170	10 mm	Brushed Stainless Steel	Stainless Steel
BPBR1010145	10 mm	Satin Chrome	Solid Brass
BPBR1012140	12 mm	Bright Polished Chrome	Solid Brass
BPBR1012170	12 mm	Brushed Stainless Steel	Stainless Steel
BPBR1012145	12 mm	Satin Chrome	Solid Brass

TECHNICAL SPECIFICATIONS

Thickness	3/8 in
Height	41.3 mm
Diameter	32 mm

APPLICATION

Ideal for signage, displays, partition, shelves and presentation.

INCLUDED PRODUCT(S)

Nylon screws maintain the glass or panel in position.

IMPORTANT INFORMATION

For safety purposes, use tempered glass. The use of power tools during installation may damage the hinges and decorative hardware. The glass must be shaped according to the section plane provided in the box. Always set the product in a suitable material. Never exceed the load or maximum size recommended by the manufacturer. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. This illustration is provided for visual reference only. Actual product may differ from the illustration. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always use the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may in no case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel. Ensure product is secured using anchors appropriate for the supporting materials. Never exceed the load or maximum-size recommended by the manufacturer. Never use a spray lubricant on this product.

DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

