



## Aluminum Wet Glaze Base Shoe

### Type of Mounting

☐ Face Mount☐ Floor Mount

### Safety Glass Thickness

☐ 10 to 12 mm☐ 19 mm

### Base section hole drilling patterns

☐ Counter Bore☐ Side Drilled

### Height

☐ 4 1/8 in☐ 4 1/4 in

### Width

☐ 2 1/2 in☐ 2 3/4 in

### Length

☐ 10 ft☐ 12 ft☐ 20 ft

### Packaging format

☐ Length of 10  
linear foot☐ Length of 12  
linear foot☐ Length of 20  
linear foot

## DESCRIPTION

### Base support for railing installation

Suitable for mortar insertion installations

## AVAILABLE PRODUCTS

Product #	Type of Mounting	Safety Glass Thickness	Base section hole drilling patterns	Height	Width	Length	Packaging format
<b>HRTV0099101210</b>	Face Mount	10 to 12 mm	Side Drilled	4 1/8 in	2 1/2 in	10 ft	Length of 10 linear foot
<b>HRTV0099101212</b>	Face Mount	10 to 12 mm	Side Drilled	4 1/8 in	2 1/2 in	12 ft	Length of 12 linear foot
<b>HRTV0099101220</b>	Face Mount	10 to 12 mm	Side Drilled	4 1/8 in	2 1/2 in	20 ft	Length of 20 linear foot
<b>HRTV0090101210</b>	Floor Mount	10 to 12 mm	Counter Bore	4 1/8 in	2 1/2 in	10 ft	Length of 10 linear foot
<b>HRTV0090101212</b>	Floor Mount	10 to 12 mm	Counter Bore	4 1/8 in	2 1/2 in	12 ft	Length of 12 linear foot
<b>HRTV0090101220</b>	Floor Mount	10 to 12 mm	Counter Bore	4 1/8 in	2 1/2 in	20 ft	Length of 20 linear foot
<b>HRTV0090191910</b>	Floor Mount	19 mm	Counter Bore	4 1/4 in	2 3/4 in	10 ft	Length of 10 linear foot

## TECHNICAL SPECIFICATIONS

<b>Recommended Location Usage</b>	Interior, Exterior
<b>Thickness</b>	3/4 in
<b>Finish</b>	Mill Finish
<b>Material</b>	Aluminum 6005-T5
<b>Glass Drilling</b>	Not Required
<b>Category</b>	Base Shoes
<b>Milling Diameter</b>	9/16 to 7/8 in
<b>Milling C/C</b>	12 in

## APPLICATION

-Typically used as the base channel for installation of glass railing systems and windscreens. -Usual maximum dimension of glass panel is 42" tall by 4-5 ft. wide. Before installation, engineer approval is required to ensure compliance with building codes.

## IMPORTANT INFORMATION

The glass must be shaped according to the section plane provided in the box. Always set the product in a suitable material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. This illustration is provided for visual reference only. Actual product may differ from the illustration. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always use the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may in no case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel. Always make sure that the product is properly installed using suitable fixings to the support material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product.

---

## DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

## PRODUCT PHOTOS

