



Double-Sided Black Foam Tape with Acrylic Adhesive for Glazing

Length

75 ft	150 ft	165 ft

Thickness

1/32 in	1/16 in	1/8 in
---------	---------	--------

Width

1/4 in 3/8 in 1/2 in	1
----------------------	---

Packaging format

	Roll of 150 inear foot	Roll of 165 linear foot
--	---------------------------	----------------------------

DESCRIPTION

Glazing Tape

Double-sided foam glazing tape is engineered with a cross-linked PE foam carrier and an acrylic adhesive system.

Especially designed for window glazing applications, this product's unique construction makes it easy and pleasant to apply.

ADVANTAGES AND BENEFITS

- Good resistance to temperature, weather, oxidation, and UV - Seals well against water, dust, and light

AVAILABLE PRODUCTS

Product #	Length	Thickness	Width	Packaging format
703GL183890	75 ft	1/8 in	3/8 in	Roll of 75 linear foot
703GL181290	75 ft	1/8 in	1/2 in	Roll of 75 linear foot
703GL1161490	150 ft	1/16 in	1/4 in	Roll of 150 linear foot
703GL1163890	150 ft	1/16 in	3/8 in	Roll of 150 linear foot
703GL1161290	150 ft	1/16 in	1/2 in	Roll of 150 linear foot
703GL1323890	165 ft	1/32 in	3/8 in	Roll of 165 linear foot



TECHNICAL SPECIFICATIONS

Usage/Activity	Window Manufacturers, Residential Windows, Construction, Industrial, General
Optimal adhesion on	Vinyl and PVC
Adhesive type	Multi-Purpose Acrylic
Backing/Liner	Blue Polypropylene
Adhesive Strength oz/in	110 oz
Standards and Certifications	AAMA
Color/Finish	Black
Manufacturing Material	Polyethylene

APPLICATION

-Window glazing application -Application temperature range; -20°C to 120°C

DISCLAIMER

AAMA certified suitable for glazing purpose

PRODUCT PHOTOS

