

Rim Type Panic Bars - 336 Series

Standards and Certifications


ANSI BHMA
A156.3

UL10C / UBC
7-2-1997 /
ANSI BHMA
A156.3

Fire-Rating

1h30

Not Certified

Retaining

Not an Option

Standard 1/4
Turn Allen
Type

DESCRIPTION

Designed for light duty applications, our 336 series panic bars are built to ANSI Grade 2 standards.

ADVANTAGES AND BENEFITS

- Cylinders: 6-pin standard where applicable - Material: push bar in extruded anodized aluminum, spring in stainless steel - Latchbolts: stainless steel - Deadbolts: stainless steel - Finish: push bar anodized, cover painted

AVAILABLE PRODUCTS

Product #	Standards and Certifications	Fire-Rating	Retaining
336ERAL	ANSI BHMA A156.3	Not Certified	Standard 1/4 Turn Allen Type
336EFRAL	UL10C / UBC 7-2-1997 / ANSI BHMA A156.3	1h30	Not an Option

TECHNICAL SPECIFICATIONS

Door Width Requirements	30 to 36 in
Minimum Frame Width	Min. 2 1/2 in
Grade	2
Door Thickness	1 3/4 in
Backset	2 3/4 in
Strike	5/8 in
Projection Pushpad Depressed	1 7/8 in
Projection Pushpad Neutral	2 1/2 in
Color/Finish	Satin Aluminum
Handing Position / Opening Side	Reversible for Left or Right
Mounting Hardware	Included
Mounting Height	40 5/16 in
Dogging	1/4 in
Latchbolt Throw	3/4 in
Deadbolt Throw	1/2 in
Strike	1/2 to 5/8 in
Width	33 1/4 in
Finish Warranty	5 Years
Mechanical Warranty	10 Years

IMPORTANT INFORMATION

- Limited mechanical warranty of 10 years, 5-year limited warranty on finish

PRODUCT PHOTOS

