



Wedge Hanger

Finish

Black

White

Safe Working Load

5.5 lb

22 lb

55 lb

Length - Overall Dimensions

38 mm

57 mm

75 mm

Width

26 mm

38 mm

51 mm

Projection

1/4 in

1/2 in

DESCRIPTION

Use indoors or outdoors on vertical or slanted surfaces.

Available in three sizes and two colors, black and white. The fastener consists of two parts, one male and one female. The female component is available in open and closed versions.

ADVANTAGES AND BENEFITS

Offers endless possibilities! - Easily hang up your mailbox and take it down for vacations. - Change your birdhouse between seasons. - Take down your dartboard and replace it with a basketball net. - Put up "Closed" or "Vacancy" signs for your business. - Need a little variety at home? Quickly change your paintings and pictures. - Place loudspeakers on walls with the open fastener or even on ceilings with the closed fastener. - Take down your medicine cabinet for quick cleaning.

AVAILABLE PRODUCTS

Product #	Finish	Safe Working Load	Length - Overall Dimensions	Width	Projection
45361FBR	Black	55 lb	75 mm	51 mm	1/2 in
45341WR	White	5.5 lb	38 mm	26 mm	1/4 in
45351WR	White	22 lb	57 mm	38 mm	1/2 in
45361WR	White	55 lb	75 mm	51 mm	1/2 in

TECHNICAL SPECIFICATIONS

Type	Universal
Screws	Included
Material	Nylon
Screws/Nails	Included

APPLICATION

Fastening and mounting with closed female component: The closed fastener can be used outdoors as well as indoors on both vertical and slanting surfaces and even on ceilings. The male component is mounted on the bearing surface, while the female component is attached to the object to be suspended. Both components are connected by placing the female component at an angle of 90° to the male part, then turning the object 90°. Mounting can be adjusted by turning the object lightly. Stand-off studs are mounted to the lower corners of the object before hanging. Fastening and mounting with open female component: The open fitting can be used outdoors as well as indoors on both vertical and slanting surfaces. The male component is mounted on the bearing surface, while the female component is attached to the object to be suspended. The object in question is fastened by placing the female component just above the male component, then letting the two parts glide together as a single unit. Mounting can be adjusted by turning the object lightly. Stand-off studs are mounted to the lower corners of the object before hanging. *** Screws for the most popular applications are included. Other screw lengths can be used if necessary for your application, but are not included. *** Does not include wall plugs for mounting to drywall or anchors for mounting to concrete and stone.

IMPORTANT INFORMATION

WARRANTY - The manufacturer and seller guarantees this product to be free from manufacturing defects. Proper installation and performance of this product is dependent upon varying conditions and quality of materials and workmanship of the wall it is being installed onto. Therefore, it is the responsibility of the user to ensure that the wall is suitable for the application, is in good condition, and that the object being hung is static and placed out of reach of children or where it could cause injury to people. The manufacturer's and seller's warranty, expressed or implied, is limited to the sale price of any defective goods. The manufacturer and seller shall in no event be liable for incidental or consequential damages resulting from the use or misuse of this product.

PRODUCT PHOTOS

