



Lift-Off Gravity-Closing 90° Wall-to-Glass Hinge

Finish



Mounting Side



DESCRIPTION

Gravity-closing function

This 90° gravity-closing hinge is designed to be installed from wall to glass.

ADVANTAGES AND BENEFITS

Provides an exceptionally unobstructed and clear view for any outdoor space. Weather resistant. Factory lubricated.

AVAILABLE PRODUCTS

Product #	Finish	Mounting Side
PGLOH1009003140	Bright Polished Chrome	Left Side
PGLOH1009002140	Bright Polished Chrome	Right Side
PGLOH1009002195	Brushed Nickel	Right Side

TECHNICAL SPECIFICATIONS

Material	Solid Brass
Glass Thickness	8 to 12 mm
Mounting Method	Glass-to-Wall/90°
Height	90 mm
Length	60 mm
Width	40 mm
Weight Capacity for 2 Hinges	Max. 45 kg
Recommended Location Usage	Interior, Exterior
Usage	Heavy-Duty
Milling Diameter	12 mm
Load Capacity	Max. 45 kg
Max. Door Width for 2 Hinges	Max. 1 000 mm
Milling C/C	50 mm



APPLICATION

Installs glass-to-wall -Not for use on pool gates. They are not designed to meet swimming pool regulations or codes which require a force closing hinge with at least five pounds of closing force.

IMPORTANT INFORMATION

For safety purposes, use tempered glass. The use of power tools during installation may damage hinges and decorative hardware. The glass must be shaped according to the instructions provided in the box. Always set the product in a suitable material. Never exceed the load or maximum size recommended by the manufacturer. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. This illustration is provided for visual reference only. Actual product may differ from the illustration. Order hardware before starting the job. Always use the instructions inside the package since the manufacturer reserves the right to change product and information without notice. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may in no case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. These are self-centering hinges that center with the downward force of gravity and swing both ways. They are not designed to meet swimming pool regulations or codes which require a force closing hinge with at least five pounds of closing force. Installation must be done by qualified personnel.

DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

