



## Double Sided Polyester Tape With Red Poly Liner

### Optimal adhesion on

Painted Metal  
/ Glass and  
Mirror

Metal /  
Painted Metal  
/ Glass and  
Mirror / Vinyl  
and PVC /  
Plastic

### Usage/Activity

Construction /  
Industrial /  
General

Construction /  
Industrial /  
General /  
Shower Head  
Assembly

### Breaking Strength lb/in

20 lb

### Adhesive Strength oz/in

65 oz

80 oz

### Manufacturing Material

Acrylic foam

Polyester

### Thickness

0.008 in

1.016 mm

### Width

6 mm

9 mm

12 mm

24 mm

48 mm

## DESCRIPTION

It is an 8 mil, double sided polyester tape offering excellent plasticizer migration resistance and good adhesion under high temperature conditions.

## ADVANTAGES AND BENEFITS

Offers superior immediate adhesion performance to safe reliable sticking strength even to low energy substrates like PP or PE Provides excellent high shear resistance balance, quite good initial tack and superior adhesion level Provides superior durability Supports the process-ability and die-cutting ability

## AVAILABLE PRODUCTS

Product #	Optimal adhesion on	Usage/Activity	Breaking Strength lb/in	Adhesive Strength oz/in	Manufacturing Material	Thickness	Width
<b>703HA3641211</b>	Painted Metal / Glass and Mirror	Construction / Industrial / General / Shower Head Assembly	20 lb	80 oz	Acrylic foam	1.016 mm	12 mm
<b>703UB1643811</b>	Metal / Painted Metal / Glass and Mirror / Vinyl and PVC / Plastic	Construction / Industrial / General		65 oz	Polyester	0.008 in	9 mm
<b>703UB1641211</b>	Metal / Painted Metal / Glass and Mirror / Vinyl and PVC / Plastic	Construction / Industrial / General		65 oz	Polyester	0.008 in	12 mm
<b>703UB1640111</b>	Metal / Painted Metal / Glass and Mirror / Vinyl and PVC / Plastic	Construction / Industrial / General		65 oz	Polyester	0.008 in	24 mm
<b>703UB1640211</b>	Metal / Painted Metal / Glass and Mirror / Vinyl and PVC / Plastic	Construction / Industrial / General		65 oz	Polyester	0.008 in	48 mm
<b>703HA3641411</b>	Metal / Painted Metal / Glass and Mirror / Vinyl and PVC / Plastic	Construction / Industrial / General	20 lb	65 oz	Polyester	1.016 mm	6 mm

## TECHNICAL SPECIFICATIONS

<b>Backing/Liner</b>	Red polypropylene
<b>Adhesive type</b>	Multi-Purpose Acrylic
<b>Color/Finish</b>	Translucent
<b>Length</b>	33 m

## APPLICATION

Membrane switches, plastic moulding, insulation film, various types of film Nameplates and metal plates

**PRODUCT PHOTOS**

---

