


PanelGrip®2 Locking Mechanism

Safety Glass Thickness

12 mm

19 mm

Finish



DESCRIPTION

Patented glass panel mounting system.

The patented PanelGrip®2 System utilizes a unique locking mechanism of high-strength aluminum and PVC isolators combined with a specially designed aluminum shoe molding.

Isolator assembly is adjustable to accommodate 1/2" through 13/16" glass.

Glass Deduction = 15/16". 10 ft/lbs of torque.

Simple to install and needs nothing other than an Allen key.

Can be fixed on the inside of the base shoe in 35 cm (14") intervals from center to center.

ADVANTAGES AND BENEFITS

No mixing or pouring of cement or Rockite required. Easy leveling of glass as well as easy replacement of glass panels.

AVAILABLE PRODUCTS

Product #	Safety Glass Thickness	Finish
HRA42PG212	12 mm	Black
HRA42PG219	19 mm	White

TECHNICAL SPECIFICATIONS

Height	2 7/8 in
Width	0.562 in
Length	2 1/2 in
Material	Aluminum

IMPORTANT INFORMATION

Space plastic isolators a maximum of 4" on center with a maximum of 4' in from the left and right edges of each panel (4 isolators per 4-foot panel). The client is responsible for engineering and related safety inspections. Always set the product in a suitable material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. This illustration is provided for visual reference only. Actual product may differ from the illustration. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always use the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may in no case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel.

DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

