



Rolling System for Sliding Door System Aqua01

Finish

Black Nickel

Bright
Polished
Chrome

Brushed
Nickel

DESCRIPTION

Allows to open and close the door

Replacement casters for sliding door system for frameless glass showers. Similar to the principle of standoffs, these casters keep the glass door on the track system for sliding doors.

ADVANTAGES AND BENEFITS

Available in the most popular finishes on the market. Suitable for various thicknesses of tempered glass.

AVAILABLE PRODUCTS

Product #	Finish
705AQUA01DRR900	Black Nickel
705AQUA01DRR171	Bright Polished Chrome
705AQUA01DRR170	Brushed Nickel

TECHNICAL SPECIFICATIONS

Application	Single Sliding
Diameter	39 mm
Milling Diameter	16 mm
Glass Thickness	8 to 10 mm
Brand	Riveo
Material	Stainless Steel: 304

APPLICATION

Supports the glass door in a face mount, allowing it to be opened and closed. Installs directly on the top part of the header of the sliding door system. Simply place the opening of the face of the caster on the track. Glass drilling is required for use.

INCLUDED PRODUCT(S)

Pair of casters, mounting pieces and seals.

IMPORTANT INFORMATION

For safety purposes, use tempered glass. The glass must be shaped according to the section plane provided in the box. This illustration is provided for visual reference only. Actual product may vary. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always follow the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may not in any case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must always be done by qualified personnel.

DISCLAIMER

The preceding information, as well as any technical recommendation given in writing or verbally, whether based on tests or not, is provided to the best of our knowledge. Recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products, as well as the execution of projects based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

