



Back-to-Back Ladder Handle with Wood Insert

Center to Center Drilling (Spacing)

12 in

24 in

36 in

Diameter

32 mm

38 mm

Height

24 in

36 in

48 in

Projection

70 mm

78 mm

DESCRIPTION

Wooden handle

This handle can be used on hinged or sliding doors. Its modern and sophisticated design will add a personal touch to your commercial development projects.

ADVANTAGES AND BENEFITS

The black wooden handle provides a refined and versatile feature that is suitable for all environments. The handle can be installed either on a glass or wood door.

AVAILABLE PRODUCTS

Product #	Center to Center Drilling (Spacing)	Diameter	Height	Projection
705241232BW170	12 in	32 mm	24 in	70 mm
705362432BW170	24 in	32 mm	36 in	70 mm
705483638BW170	36 in	38 mm	48 in	78 mm

TECHNICAL SPECIFICATIONS

Color/Finish	Black, Stainless Steel
Door Type	Glass, Wood, Architectural
Glass Thickness	8 to 12 mm
Door Thickness	35 to 50 mm
Material	Stainless Steel 304, Wood
Type	Round
Washers Diameter	32 mm
Usage	Sliding Door, Hinge Door, Commercial Door
Milling Diameter	12 mm
Function	Back-to-Back Pull Handle
Screw/Nail	Included, M8

APPLICATION

Ideal for offices, conference rooms, exhibition halls and shopping centers

INCLUDED PRODUCT(S)

Installation hardware for mounting on glass and wood included.

IMPORTANT INFORMATION

For safety purposes, use tempered glass. Glass drilling is required for use. This illustration is provided for visual reference only. Actual product may vary. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always follow the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may not in any case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must always be done by qualified personnel.

DISCLAIMER

The preceding information, as well as any technical recommendation given in writing or verbally, whether based on tests or not, is provided to the best of our knowledge. Recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products, as well as the execution of projects based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

