





1 1/4" (32 mm) Diameter Back-to-Back Ladder Handle

Color/Finish



Center to Center Drilling (Spacing)

6 in

12 in

24 in

36 in

48 in

60 in

Glass Thickness

8 to 12 mm

10 to 12 mm

Height

12 in

24 in

36 in

48 in

60 in

72 in

Projection

72 mm

76 mm

Washers Diameter

32 mm

Usage

Sliding Door /
Hinge Door

Shower Door
/ Sliding Door
/ Hinge Door

Milling Diameter

14 mm

16 mm

Screw/Nail

Included / M6

Included / M8

DESCRIPTION

Door handle

AVAILABLE PRODUCTS

Product #	Color/Finish	Center to Center Drilling (Spacing)	Glass Thickness	Height	Projection	Washers Diameter	Usage	Milling Diameter	Screw/Nail
705362432169	Black Stainless Steel	24 in	8 to 12 mm	36 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8
705483632169	Black Stainless Steel	36 in	8 to 12 mm	48 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8
705604832169	Black Stainless Steel	48 in	8 to 12 mm	60 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8
705726032169	Black Stainless Steel	60 in	8 to 12 mm	72 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8
701DH2R10324900	Matte Black	12 in	8 to 12 mm	24 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8
701DH2R10336900	Matte Black	24 in	8 to 12 mm	36 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8
701DH2R10348900	Matte Black	36 in	8 to 12 mm	48 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8
701DH2R10360900	Matte Black	48 in	8 to 12 mm	60 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8
701DH2R10372900	Matte Black	60 in	8 to 12 mm	72 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8
70512632170	Stainless Steel	6 in	8 to 12 mm	12 in	72 mm	32 mm	Shower Door / Sliding Door / Hinge Door	14 mm	Included / M8
CDLADDER12	Stainless Steel	6 in	10 to 12 mm	12 in	76 mm		Shower Door / Sliding Door / Hinge Door	16 mm	Included / M6
705241232170	Stainless Steel	12 in	8 to 12 mm	24 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8
705362432170	Stainless Steel	24 in	8 to 12 mm	36 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8
705483632170	Stainless Steel	36 in	8 to 12 mm	48 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8
705604832170	Stainless Steel	48 in	8 to 12 mm	60 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8
705726032170	Stainless Steel	60 in	8 to 12 mm	72 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8
70512632171	Chrome / Polished Stainless Steel	6 in	8 to 12 mm	12 in	72 mm	32 mm	Shower Door / Sliding Door / Hinge Door	14 mm	Included / M8

Product #	Color/Finish	Center to Center Drilling (Spacing)	Glass Thickness	Height	Projection	Washers Diameter	Usage	Milling Diameter	Screw/Nail
CDLADDER12PS	Chrome / Polished Stainless Steel	6 in	10 to 12 mm	12 in	76 mm		Shower Door / Sliding Door / Hinge Door	16 mm	Included / M6
705241232171	Chrome / Polished Stainless Steel	12 in	8 to 12 mm	24 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8
705362432171	Chrome / Polished Stainless Steel	24 in	8 to 12 mm	36 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8
705483632171	Chrome / Polished Stainless Steel	36 in	8 to 12 mm	48 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8
705604832171	Chrome / Polished Stainless Steel	48 in	8 to 12 mm	60 in	72 mm	32 mm	Sliding Door / Hinge Door	14 mm	Included / M8

TECHNICAL SPECIFICATIONS

Diameter	32 mm
Door Type	Glass, Wood, Architectural
Door Thickness	35 to 50 mm
Material	Stainless Steel 316
Type	Round
Function	Back-to-Back Pull Handle

IMPORTANT INFORMATION

This illustration is provided for visual reference only. Actual product may vary. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always follow the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may not in any case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must always be done by qualified personnel. Make sure that the product is properly installed using suitable fixtures on the support material. Never exceed the maximum load or size recommended by the manufacturer. Never use a spray lubricant on this product. Clean with a soft cloth and soap that is ammonia-free and nonabrasive. Always use a dry cloth to remove debris, dust and residues (sawdust and/or aluminum dust) from rails before installing hangers.

DISCLAIMER

The preceding information, as well as any technical recommendation given in writing or verbally, whether based on tests or not, is provided to the best of our knowledge. Recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products, as well as the execution of projects based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

