



## Adjustable Glass Connector, with Square Ends



### Safety Glass Thickness

10 to 12 mm

12 to 15 mm

16.76 to 21.52  
mm

### Finish



### Width

26 mm

34 mm

40 mm

### Length

85 mm

92 mm

92 mm

## DESCRIPTION

### Adjustable connector for glass mounting

Adjustable bracket to connect two glass panels.

## ADVANTAGES AND BENEFITS

Provides a clear and open view free of visual obstructions. Suitable for various glass types and thicknesses. No glass fabrication required.

## AVAILABLE PRODUCTS

Product #	Safety Glass Thickness	Finish	Width	Length
SSPFEBADJ169	10 to 12 mm	Black Stainless Steel	26 mm	92 mm
SSPFEBADJGB	10 to 12 mm	Graphite Black	26 mm	92 mm
SSPFEBADJMB	10 to 12 mm	Matte Black	26 mm	92 mm
SSPFEBADJ900	10 to 12 mm	Matte Black	26 mm	92 mm
SSPFEBADJS	10 to 12 mm	Satin Stainless Steel	26 mm	92 mm
SSPFEBADJ170	10 to 12 mm	Stainless Steel	26 mm	92 mm
SSPFEBADJ1	12 to 15 mm	Satin Stainless Steel	34 mm	85 mm
SSPFEBADJ1170	12 to 15 mm	Stainless Steel	34 mm	85 mm
SSPFEBADJ2	16.76 to 21.52 mm	Satin Stainless Steel	40 mm	92 mm
SSPFEBADJ2170	16.76 to 21.52 mm	Stainless Steel	40 mm	92 mm

---

## TECHNICAL SPECIFICATIONS

Type of Mounting	Glass Mount
Height	25 mm
Material	Stainless Steel: Duplex 2205
Glass Drilling	Not Required
Recommended Location Usage	Interior, Exterior, Coastal
Category	Glass Connectors
Thread Type	M10

## APPLICATION

Fits perfectly with glass railing projects such as staircases and balusters.

## IMPORTANT INFORMATION

For safety purposes, use tempered glass. This illustration is provided for visual reference only. Actual product may vary. The manufacturer reserves the right to change product and information without notice. Always follow the instructions inside the package. Installation must always be done by qualified personnel.

## DISCLAIMER

The preceding information, as well as any technical recommendation given in writing or verbally, whether based on tests or not, is provided to the best of our knowledge. Recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products, as well as the execution of projects based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

**PRODUCT PHOTOS**

