



90° Glass to Wall Connector, with Square Ends

Safety Glass Thickness



Finish



Width

| 24 mm 34 mm 40 mm |
|-------------------|
|-------------------|

Length

| 55 mm | 65 mm |
|-------|-------|
|-------|-------|

DESCRIPTION

Corner connector for glass mounting

Fixed bracket to connect a glass panel to a wall. Forms a 90° right angle.

ADVANTAGES AND BENEFITS

Provides a clear and open view free of visual obstructions. Suitable for various glass types and thicknesses. No glass fabrication required.

AVAILABLE PRODUCTS

| Product # | Safety Glass Thickness | Finish | Width | Length |
|--------------|------------------------|-----------------------|-------|--------|
| SSPFEBWALLGB | 10 to 12 mm | Graphite Black | 24 mm | 65 mm |
| SSPFEBWALLS | 10 to 12 mm | Satin Stainless Steel | 24 mm | 65 mm |
| SSPFEBWALL1 | 12 to 15 mm | Satin Stainless Steel | 34 mm | 55 mm |
| SSPFEBWALL2 | 16.76 to 21.52 mm | Satin Stainless Steel | 40 mm | 55 mm |



TECHNICAL SPECIFICATIONS

| Type of Mounting | Wall Mount | |
|----------------------------|------------------------------|--|
| Height | 25 mm | |
| Material | Stainless Steel: Duplex 2205 | |
| Glass Drilling | Not Required | |
| Recommended Location Usage | Interior, Exterior, Coastal | |
| Category | Glass Connectors | |

APPLICATION

Fits perfectly with glass railing projects such as staircases and balusters.

IMPORTANT INFORMATION

For safety purposes, use tempered glass. This illustration is provided for visual reference only. Actual product may vary. The manufacturer reserves the right to change product and information without notice. Always follow the instructions inside the package. Installation must always be done by qualified personnel.

DISCLAIMER

The preceding information, as well as any technical recommendation given in writing or verbally, whether based on tests or not, is provided to the best of our knowledge. Recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products, as well as the execution of projects based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

