

## C1000 Series Concealed Overhead Door Closer

### Type

105° Non-Hold Open

90° Hold Open

### DESCRIPTION

Overhead concealed closers control door opening and closing, while providing an aesthetically pleasing design option for both interior and exterior use. Used with aluminum doors and frames, providing years of maintenance-free performance.

- Center-hung for single or double action doors
- Side loading and end loading installation
- Dual valves for latching and closing speed adjustment
- Interchangeable with other brands of hole patterns
- All-weather fluid
- Fits inside standard aluminum frame header for improved aesthetics and increased security

### ADVANTAGES AND BENEFITS

All-weather fluid Adjustable closing and latching speed Interchangeable with other brands of hole patterns

### AVAILABLE PRODUCTS

Product #	Type
24731050105BC	105° Non-Hold Open
2473105090HBC	90° Hold Open

### TECHNICAL SPECIFICATIONS

Force #	#5
Weight Capacity	60 to 85 kg
Spindle Length	3/4 in
Standards and Certifications	UL, UL10C, cULus, ANSI A156.4 Grade 1
Max. Door Width	1 100 mm
Width	94 mm
Length	282 mm
Material	Cast Iron

### APPLICATION

For use with aluminum doors and frames For both center-hung (single or double acting) and offset doors For interior and exterior use

PRODUCT PHOTOS

