



Riveo Pro Beveled Heavy-Duty GTW Hinge w/ "H" Back Plate

Finish

Bright Polished Chrome

Brushed Nickel

Matte Black

Matte Oiled Bronze

DESCRIPTION

This self-closing hinge is designed to install a glass door to an adjacent wall. The H-shaped mounting plate allows the glass to be cut deeper in order to install the panel closer to the wall. Riveo Pro offers the widest range of styles and finishes to complement any project.

ADVANTAGES AND BENEFITS

Self-closing from 30°

AVAILABLE PRODUCTS

Product #	Finish
SH1HBV90W140	Bright Polished Chrome
SH1HBV90W195	Brushed Nickel
SH1HBV90W900	Matte Black
SH1HBV90WORB	Matte Oiled Bronze

TECHNICAL SPECIFICATIONS

Angle	90°
Application	Corner Shower, Door, Door and Panel
Collection	Riveo Pro
Glass Thickness	10 to 12 mm
Brand	Riveo
Material	Solid Brass/Stainless Steel Pin & Spring
Max. Glass Width for 2 Hinges	Max. 30 in
Max. Glass Width for 3 Hinges	Max. 36 in
Mounting Method	Wall Mount
Max. Glass Weight for 2 Hinges	Max. 45 kg
Max. Glass Weight for 3 Hinges	Max. 68 kg
Style	Beveled
Hinge Type	Standard
Usage	Heavy-Duty

APPLICATION

Designed to be used with several thicknesses of tempered glass. Regular-duty models require "mouse-ear" type glass milling for installation. Heavy-duty models require square type glass milling for installation. Light-duty models require square type glass milling for installation.

IMPORTANT INFORMATION

For safety purposes, use tempered glass. The use of power tools during installation may damage the hinges and decorative hardware. The glass must be shaped according to the section plane. Clean with a soft cloth and soap that is ammonia-free and non-abrasive. This illustration is provided for visual reference only. Actual product may differ from the illustration. Always order hardware before starting the job. Always follow the instruction manual provided in the packaging. The manufacturer reserves the right to change product and information without notice. The drawings and technical instructions show mounting examples using hardware from different manufacturers. Richelieu expressly declines all responsibility for any design or construction, whether based on these documents or not. Installation must be done by qualified personnel. Always set the product in a suitable material. Never exceed the load or maximum size recommended by the manufacturer. Do not use aerosol lubricant on these products.

DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

