



Riveo Square GTG Hinge 180°

Finish

Brushed Nickel

Chrome

Matte Black

DESCRIPTION

This self-closing hinge is designed for installing a glass door on an adjacent wall. Its ergonomic design allows the door to open up to 180° and close automatically. The hinge is corrosion-resistant, made of solid brass with a stainless steel rod and spring. This hinge is perfect for corner shower, door, and panel jobs.

ADVANTAGES AND BENEFITS

Self-closing from 15° angle

AVAILABLE PRODUCTS

Product #	Finish
SH3SQ180G195	Brushed Nickel
SH3SQ180G140	Chrome
SH3SQ180G900	Matte Black

TECHNICAL SPECIFICATIONS

Angle	180°
Application	Corner Shower, Door and Panel
Collection	Riveo
Glass Thickness	8 to 10 mm
Brand	Riveo
Material	Solid Brass/Stainless Steel Pin & Spring
Max. Glass Width for 2 Hinges	Max. 750 mm
Max. Glass Width for 3 Hinges	Max. 813 mm
Mounting Method	Glass Mount
Max. Glass Weight for 2 Hinges	Max. 45 kg
Max. Glass Weight for 3 Hinges	Max. 54 kg
Style	Square
Hinge Type	Standard
Usage	Regular

APPLICATION

Designed to be used with several thicknesses of tempered glass. "Mouse-ear" type glass milling is required for installation.

IMPORTANT INFORMATION

For safety purposes, use tempered glass. The glass must be shaped according to the section plane. Always set the product in a suitable material. Never exceed the load or maximum size recommended by the manufacturer. Always order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always follow the instruction manual provided in the packaging. The drawings and technical instructions show mounting examples using hardware from different manufacturers. Richelieu expressly declines all responsibility for any design or construction based on these documents. Installation must be done by qualified personnel.

DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

