



TILT-LOCK(TM) Adjustable Top-Mount Spigot

Finish



DESCRIPTION

Allows for glass to be tilted 2° backward or forward

Suitable for glass from 12 mm to 17.52 mm (15/32" to 11/16") thick.

ADVANTAGES AND BENEFITS

- All adjustments can be achieved from one side - Pressure plate model - Slotted base plate holes - Cover plate included - Made of duplex 2205 low carbon ultramarine grade stainless steel, allowing for superior corrosion resistance as well as more than double the yield strength and 20% more tensile strength than 316 grade stainless steel

AVAILABLE PRODUCTS

Product #	Finish
SSSPIGOTAGB	Graphite Black
SSSPIGOTADJ	Satin Stainless Steel

TECHNICAL SPECIFICATIONS

Safety Glass Thickness	12 to 17.52 mm
Recommended Location Usage	Exterior, Coastal
Height	160 mm
Material	Stainless Steel: Duplex 2205
Glass Drilling	Not Required
Panel Height	Max. 48 in
Panel Width	Min. 26 in
Type of Mounting	Floor Mount
Category	Spigots

APPLICATION

Highly suitable for use in outdoor structures with high degree of corrosion due to chlorine and/or sulfur dioxide load; high humidity, accumulation of harmful substances (e.g., coastal regions and swimming pool environments) - Fully engineered for the National Building Code of Canada - Tested up to 3 kN

IMPORTANT INFORMATION

For safety purposes, use tempered glass. This illustration is provided for visual reference only. Actual product may vary. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always follow the instructions inside the package. The customer may not in any case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must always be done by qualified personnel. Make sure that the product is properly installed using suitable fixtures on the support material. Never exceed the maximum load or size recommended by the manufacturer.

DISCLAIMER

The preceding information, as well as any technical recommendation given in writing or verbally, whether based on tests or not, is provided to the best of our knowledge. Recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use, or processing of our products, as well as the execution of projects based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

