




Transition Line Posts - Frameless

Finish



Material

Stainless Steel 304

Stainless Steel 316

DESCRIPTION

For transitioning from 36" stairs to a 42" landing in a line

ADVANTAGES AND BENEFITS

- Fully engineered and designed for indoor and outdoor projects - Fully welded end caps provide an open and frameless look for an unobstructed view - Fully welded 4" solid cast stainless steel base plates with flat push-fit base plate covers - Large square glass clamps secured by M8x20 stainless steel fasteners through flow-drilled and tapped holes to the posts included - Suitable for 10 or 12 mm glass

AVAILABLE PRODUCTS

Product #	Finish	Material
SSPEFT36T42B	Satin Black	Stainless Steel 304
SSPEFT36T42S	Satin Stainless Steel	Stainless Steel 316

TECHNICAL SPECIFICATIONS

Configuration	Transition Post
Mounting Position	Landing
Type of Mounting	Floor Mount
Height	42 1/8 in
Safety Glass Thickness	10 to 12 mm
Recommended Location Usage	Interior, Exterior
Baluster Post Type	Square Tube

INCLUDED PRODUCT(S)

- Post - Glass clamps with M8 x 20 fasteners - Gaskets for 10 or 12 mm glass - Base plate - Base plate cover

IMPORTANT INFORMATION

For safety purposes, use tempered glass. Configurations show the positions and sizes of posts only and do not include the placement of a handrail. For stairs, a handrail is required to comply with code. Please consult with local building codes to adhere to requirements. This illustration is provided for visual reference only. Actual product may vary. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always follow the instructions inside the package. The customer may not in any case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must always be done by qualified personnel. Make sure that the product is properly installed using suitable fixtures on the support material. Never exceed the maximum load or size recommended by the manufacturer.

DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally, or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use, or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

